

Model PRMLxT1L

Preamplifier for SoundTrack LxT® Sound Level Meter

The Larson Davis PRMLxT1L is a microphone preamplifier for use with electret microphones with a Larson Davis SoundTrack LxT® Sound Level Meter. The preamplifier requires very little supply current and operates over wide temperature and humidity ranges. It is for use with 50mV/Pa sensitivity microphones up to a Sound Pressure Level of 121dB. The preamplifier will drive 200 feet of cable to 20kHz.

SPECIFICATIONS

FUNCTION	SPECIFICATION	REMARKS
Frequency Response	4Hz-40kHz	(+ 0.1dB/- 0.5)dB
Attenuation	1.2dB	Typical
Preamplifier Sensitivity	-27.2dB re1V/Pa	±3dB re1V/Pa
Input Impedance	10GΩ//3pF	Typical
Output Impedance	50Ω	Typical
Maximum Output Voltage	2.8Vpp	121dB peak for microphones with 50mV/Pa sensitivity
Maximum Output Current	10mA peak	
Distortion	Harmonics < -67dBC	0.7V rms output @ 1kHz
Output Slew Rate	2V/μS	Typical
Electronic Noise	- 1.8μV A-weighted - 3.2μV Flat (20Hz-20kHz)	Typical for 18pF microphone
Power Supply Voltage	6 to 15 Volts	
DC Output Level	0.5 X Power Supply Voltage	
Power Supply Current	1.3mA	Typical
Temperature Sensitivity	< ± 0.05 dB (14deg to 122 deg F)	-10 deg to +50 deg C
Humidity Sensitivity	< ± 0.05 dB (0-90% RH)	Non-condensing @104°F
Dimensions	0.5" dia x 2.88"L	12.7mm dia x 73mm L
Compatibility	Larson Davis 377B02 or any 1/2" electret microphones with about 50mV/Pa sensitivity	ADP043 or ADP008 adaptors for 1/4" or 1" microphones



Total Customer Satisfaction Guaranteed

Larson Davis, Inc.

3425 Walden Avenue, Depew, NY 14043-2495 USA

Toll Free: 888-258-3222 Phone: 716-926-8243 Fax: 716-926-8215

Email: sales@LarsonDavis.com www.LarsonDavis.com

ISO 9001:2000 CERTIFIED

ICP is a registered trademark of PCB Group, Inc. All other trademarks are property of their respective owners. In the interest of constant product improvement, specifications are subject to change without notice.

© 2006 Larson Davis, Inc. All rights reserved.

Printed in U.S.A.

Larson Davis provides a complete line of acoustic and vibration measurement tools including dosimeters, sound level meters, real time analyzers, pre-amplifiers, calibrators, and microphones.